



Rotonivo[®] 4000

Rotating level limit switch

The reliable solution with a plastic housing – versatile, robust construction, also for applications in hazardous locations



Rotonivo® 4000



- Plastic version
- Suitable for nearly all bulk goods
- Simple and reliable measuring principle, easy, fast installation

Application: The Rotonivo® 4000 can be used as a full, demand or empty detector in bulk good silos depending on needs. It is mainly suited for lower mechanical loads in a variety of materials, e.g. cement, detergent, feed, chalk, grains, plastic granulate and much more.

RN 4001 Standard

Full, demand, empty detector
Standard design, vertical, horizontal and oblique installation
Extension up to 1000 mm




RN 4001 Pend. Shaft

Full detector
Design with option pendulum shaft, vertical installation



RN 4001 Rope

Full detector
Design with rope extension, vertical installation



Technical Data

Housing	Plastic PA 6 GF, IP 66	
Certificates	ATEX II 1/2D, IECEx, TR-CU	
Process temperature	-40°C up to +80°C (-40°F up to +176°F)	
Pressure	-0.9 up to +0.8 bar (-13.1 up to 11.6 psi)	
Sensitivity	From 100g/l (6lb/ft³) – adjustable in 3 steps	
Mains voltage	Universal-Voltage-Electronic AC: 24V / 48V / 115V / 230V, DC: 24V	
Process connection	G1", G1¼" and G1½", M30x1.5, M32x1.5 incl. sealing face	
Bearing	Process connection aluminium: ball bearing, dust tight Process connection plastics: slide bearing (maintenance-free, high-quality)	
Material	Process connection:	Plastic PA 6 GF, aluminium
	Shaft:	Stainless steel 1.4305
	Paddles:	Stainless steel 1.4301 Plastic PP